



Ultrafabrics Digital Binder



Collections

Ultrafabrics is redefining performance fabrics with a growing portfolio of premium and intelligent fabrics that speak to, and elevate, your senses.



Breathable Technology

Brisa

Brisa Distressed

Brisa Forecast

Brisa Frontier

Ellora

Timeless Grains

Coast

Pearlized

Promessa

Pumice

Summit

Tottori

Ultraleather

Ultraleather Anti-Static

Modern Textures

Eco Tech

Volar Bio

Wired

Uf Select

Impasto

Lino

Montage

Breathable Technology



Fabrics That Breathe

Available in a variety of grain styles, these materials provide the ultimate luxury and functionality. Engineered with a proprietary ventilation system to enhance softness, promote air circulation, and absorb unwanted noise, these fabrics breathe for the highest level of comfort and performance.

Brisa

Brisa Distressed

Brisa Forecast

Brisa Frontier



Brisa — Ultrafabrics



533-3775 Mystic Beige



533-3775 Mystic Beige



533-3019 Birch



533-3863 Cream



533-3822 Bone



533-3946 New Sand




533-3051 Ginger




533-3276 Wishbone



533-3915 Putty



533-3823 Aztec



533-5747 White



533-3277 Moon




533-5820 Quicksilver




533-3914 Bark




533-3591 Caramel



533-5703 Wrought Iron



533-6528 Clear Quartz




533-5802 Ash



533-3022 Shiitake



533-3200 Peat



533-5749 Black Onyx



533-5360 Hazy



533-4488 Olive




533-3023 Coffee Bean




533-3913 Truffle



533-3864 Desert Clay




533-6596 Ice Pink




533-3272 Iceberg



533-2698 Sterling Blue




533-4345 Honeydew




533-8269 Yukon Gold



533-1383 Pompeian Red




533-2793 Harbor Mist



533-2697 Mineral




533-4361 Lambs Ear



533-8202 Koi



533-1344 Rose Red



533-2645 Cambridge Blue




533-2621 Blue Sea



533-4510 Celery




533-8245 Cinnabar



533-1361 Beet Root



533-2694 Night Navy



533-2794 Rising Tide



533-4487 Sage




533-1373 Salsa




533-9400 Cabernet



533-2620 Evening Blue




533-2696 Skyway




533-4448 Apple Green




533-3825 Canyon




533-9378 Abyss



533-2683 Indigo




533-4303 Seaweed




533-4302 Esmeralda



Acoustics*



Breathable
Comfort



Recycled Bottles &
Renewable Fibers

Applications

Interior Upholstery

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface
65% Recycled Polyester, 35% FSC/PEFC
Certified Rayon Backing

Width:

54 Inches / 137 Centimetres

Repeat:

None

Performance

Abrasion:

ASTM D4157 / 300,000 Double Rubs (Wyzenbeek)*
BS EN ISO 12947-2 / 160,000 Rubs (Martindale)*

*meets or exceeds

Hydrolysis:

16 Weeks
ASTM D3690 Sect. 6.11 (Hydrolytic Stability)
ISO 1419 Method C (Accelerated Ageing)

Air Permeability: ASTM D737


Sound Absorption: ASTM C423

Colorfastness

Light: AATCC 16.3, 200 Hours, Grade 4
ISO 105 B02, Grade 6
Crocking: AATCC 8, Grade 4-5 Wet & Dry

Environmental

No intentionally added PFAS
SCS Indoor Advantage certified
REACH compliant
Does not contain any Red List chemicals



Scan QR code for a full list of specifications.

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.

* Acoustic applications only available in North America



ultrafabricsinc.com


Ultrafabrics® and logo, and Brisa® are registered trademarks of Ultrafabrics Inc. Made in Japan.



Brisa Distressed — Ultrafabrics




535-3274 Coyote



535-3021 Manila




535-3480 Navajo Ivory



535-3134 Buckskin




535-3340 Desert Tan




535-3271 Koala



535-3273 Shield




535-3024 Chamois




535-3980 Waylan



535-3869 Muslin




535-5679 Iron




535-3871 Moccasin




535-3137 Saddle



535-3972 Lasso




535-4512 Prairie



535-3232 Railroad



535-3231 French Roast




535-3201 Bison



535-3976 Bridle



535-3870 Pelt




535-5773 Stormy




535-3974 Steerhide



Acoustics*



Breathable
Comfort



Recycled Bottles &
Renewable Fibers

Applications

Interior Upholstery

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface
65% Recycled Polyester, 35% FSC/PEFC
Certified Rayon Backing

Width:

54 Inches / 137 Centimetres

Repeat:

8"V x 10.5"H / 203mm V x 267mm H

Performance

Abrasion:

ASTM D4157 / 300,000 Double Rubs (Wyzenbeek)*
BS EN ISO 12947-2 / 160,000 Rubs (Martindale)*

*meets or exceeds

Hydrolysis:

16 Weeks

ASTM D3690 Sect. 6.11 (Hydrolytic Stability)

ISO 1419 Method C (Accelerated Ageing)

Air Permeability:

ASTM D737

Sound Absorption:

ASTM C423

Colorfastness

Light:

AATCC 16.3, 200 Hours, Grade 4
ISO 105 B02, Grade 6

Crocking:

AATCC 8, Grade 4-5 Wet & Dry

Environmental

No intentionally added PFAS

SCS Indoor Advantage certified

REACH compliant

Does not contain any Red List chemicals



Scan QR code for a full list of specifications.

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.

* Acoustic applications only available in North America



ultrafabricsinc.com

Ultrafabrics® and logo, and Brisa® are registered trademarks of Ultrafabrics Inc. Made in Japan.



Brisa Forecast & Brisa Frontier — Ultrafabrics



393-5852 Jasper




396-3361 Mohave*




393-5750 Polar



396-3361 Mohave*




396-3024 Chamois*




393-4529 Glass




393-5852 Jasper




396-3134 Buckskin*




396-3980 Waylan*




393-4528 Sea Green



393-5875 Nimbus




396-3733 Greige*




396-3972 Lasso*



393-1331 Burnt Red




393-2542 Michigan Blue



393-5749 Black Onyx


*Brisa Frontier



Outdoor
Living



Breathable
Comfort



Recycled Bottles &
Renewable Fibers

Applications

Interior Upholstery, Exterior Upholstery

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface
65% Recycled Polyester, 35% FSC/PEFC
Certified Rayon Backing

Width:

54 Inches / 137 Centimetres

Repeat:

8"V x 10.5"H / 203mm V x 267mm H

(Brisa Frontier)

Performance

Abrasion:

ASTM D4157 / 200,000 Double Rubs (Wyzenbeek)*
BS EN ISO 12947-2 / 100,000- 140,000 Rubs (Martindale)*

*meets or exceeds

Hydrolysis:

16 Weeks
ASTM D3690 Sect. 6.11 (Hydrolytic Stability)
ISO 1419 Method C (Accelerated Ageing)

Colorfastness

Light:

ASTM G154, 1000 Hours

ISO 105 B02, Grade 8

Crocking:

AATCC 8, Grade 4-5 Wet & Dry

Chlorinated Water:

AATCC 162, Class 4-5

Perspiration:

AATCC 15, Class 5

Sea (Salt) Water:

AATCC 106, Class 4-5

Environmental

No intentionally added PFAS

SCS Indoor Advantage Gold certified

REACH compliant



Brisa Forecast



Brisa Frontier

Scan QR code
for a full list of
specifications.

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.



ultrafabricsinc.com

Ultrafabrics® and logo, and Brisa® are registered trademarks of Ultrafabrics Inc. Made in Japan.



Ellora — Ultrafabrics



604-4023 Granola



604-3563 Dawn Mist



604-3562 Soft Almond



604-4370 Icy Pear



604-4024 Whale Bone



604-4025 Coffee Cream




604-4371 Olive Drab



604-8276 Sunset Gold



604-5388 Stone Gray



604-7247 Cloud Green




604-0024 Antique Lace




604-5385 Mourning Dove



604-3564 Roast Chestnut



604-6599 Rose Water



604-7248 Ocean Teal



604-5387 Silver Charm




604-5390 Tungsten




604-8277 Auburn




604-9438 English Violet




604-2815 Faded Denim



604-5389 Outer Space




604-5386 Black Crow



604-8278 Clay Pot




604-9437 Fine Wine




604-2814 Navy Blazer



Acoustics*



Breathable
Comfort



Recycled
Water Bottles

Applications

Interior Upholstery

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface
65% Recycled Polyester, 35% Rayon Backing

Width:

54 Inches / 137 Centimetres

Repeat:

None

Performance

Abrasion:

ASTM D4157 / 300,000 Double Rubs (Wyzenbeek)*

BS EN ISO 12947-2 / 160,000 Rubs (Martindale)*

*meets or exceeds

Hydrolysis:

16 Weeks

ASTM D3690 Sect. 6.11 (Hydrolytic Stability)

ISO 1419 Method C (Accelerated Ageing)

Air Permeability:

ASTM D737

Sound Absorption:

ASTM C423

Colorfastness

Light:

AATCC 16.3, 200 Hours, Grade 4

ISO 105 B02, Grade 6

Crocking:

AATCC 8, Grade 4-5 Wet & Dry

Environmental

No intentionally added PFAS

SCS Indoor Advantage certified

REACH compliant

Does not contain any Red List chemicals



Scan QR code for a full list of specifications.

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.

* Acoustic applications only available in North America



ultrafabricsinc.com

Ultrafabrics® and logo are registered trademarks of
Ultrafabrics Inc. Made in Japan.



Timeless Grains



Enduring Designs

These collections are expertly engineered to offer optimal durability and unrivaled softness for designs that withstand the test of time. From subtle grains to pebbled textures, these timeless fabrics will add sophisticated endurance to any project.

Coast

Pearlized

Promessa


Pumice

Summit


Tottori

Ultraleather


Ultraleather Anti-Static




Coast — Ultrafabrics




640-0042 Beacon



640-0021 Snow Cap




640-6508 Dolphin



640-3797 Conch



640-3890 Cabana



640-5968 Feather



640-2579 Glacial



640-6086 Walrus Grey



640-3880 Savanna



640-3837 Bungalow



640-2590 Raindrop



640-7230 Calypso




640-5381 Black Moor



640-3881 Dusty Earth



640-3879 Terra




640-2776 Naval Blue




640-4338 Stem Green



Antimicrobial



Outdoor
Living



Recycled Bottles &
Renewable Fibers

Application

Interior Upholstery, Exterior Upholstery

Ideal for exterior marine seating and high exposure furniture applications

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface
65% Recycled Polyester, 35% FSC/PEFC
Certified Rayon Backing

Width:

54 Inches / 137 Centimetres

Repeat:

None

Performance

Abrasion:

ASTM D4157 / 400,000 Double Rubs (Wyzenbeek)*
BS EN ISO 12947-2 / 180,000 Rubs (Martindale)*

*meets or exceeds

Hydrolysis:

16 Weeks

ASTM D3690 Sect. 6.11 (Hydrolytic Stability)

ISO 1419 Method C (Accelerated Ageing)

Colorfastness

Light:

ASTM G154, 1000 Hours
SAE J2527 1500 kj, Grade 4
ISO 105 B02, Grade 8

Crocking:

AATCC 8, Grade 4-5 Wet & Dry

Chlorinated Water:

AATCC 162, Class 4-5

Perspiration:

AATCC 15, Class 5

Sea (Salt) Water:


AATCC 106, Class 4-5

Environmental

No intentionally added PFAS

SCS Indoor Advantage Gold certified

REACH compliant



Scan QR code for a full list of specifications.

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.



INDOOR ADVANTAGE GOLD
FURNITURE

ultrafabricsinc.com

Ultrafabrics® and logo are registered trademarks of Ultrafabrics Inc. Made in Japan.



Pearlized — Ultrafabrics



322-5420 Pure Silver



322-0068 Opal Dream



322-8285 Golden Ore




322-5975 Mirror



322-7228 Pink Quartz



322-9470 Lavender Agate



322-5976 Tin Man



322-3174 Mica




322-5768 Pewter




322-7225 Rose Pearl



322-1468 Ruby Crush



322-2705 Metallic Blue



322-4386 Beryl Green



322-5814 Licorice




322-8208 Spice



322-6558 Pharoah




322-2691 Midnight



322-4304 Oz



Renewable
Fibers



Application

Interior Upholstery

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface

100% FSC/PEFC Certified Rayon Backing

Width:

54 Inches / 137 Centimetres

Repeat:

None

Performance

Abrasion:

ASTM D4157 / 400,000 Double Rubs (Wyzenbeek)*

BS EN ISO 12947-2 / 180,000 Rubs (Martindale)*

*meets or exceeds

Hydrolysis:

16 Weeks

ASTM D3690 Sect. 6.11 (Hydrolytic Stability)

ISO 1419 Method C (Accelerated Ageing)

Colorfastness

Light:

AATCC 16.3, 200 Hours, Grade 4

ISO 105 B02, Grade 6

Crocking:

AATCC 8, Grade 4-5 Wet & Dry

Environmental

No intentionally added PFAS

SCS Indoor Advantage certified

REACH compliant

Does not contain any Red List chemicals



Scan QR code for a full list of specifications.

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.



ultrafabricsinc.com

Ultrafabrics® and logo are registered trademarks of Ultrafabrics Inc. Made in Japan.




Promessa — Ultrafabrics




363-5354 Galaxy Fog




363-5715 Snow




363-5818 Ash



363-5817 Shale




363-5011 Battleship




363-5845 Ebony




363-3464 Tusk




363-3463 Cocoa



363-3785 Desert Taupe




363-3391 Sparrow




363-3037 Horsehair




363-3152 Parchment




363-3142 Camel




363-2695 Aquamarine




363-7239 Aqua Spring




363-3189 Barley




363-3145 Bronze




363-2604 Stone Blue




363-7309 Malibu




363-3786 Buttered Toffee




363-1444 Fireclay




363-2792 Lake Blue




363-4362 Old Lime




363-5258 Sun Shower




363-1387 Dogwood




363-2672 Corn Flour




363-4363 Olive Moss




363-3141 Fields




363-1443 Rumba Red




363-2680 Atlantic




363-7273 Aspen Green



363-3462 Woodpecker



363-9414 Merlot



363-9387 Moroccan Fig



Application

Interior Upholstery

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface
65% Recycled Polyester, 35% FSC/PEFC
Certified Rayon Backing

Width:

54 Inches / 137 Centimetres

Repeat:

None

Performance

Abrasion:

ASTM D4157 / 400,000 Double Rubs (Wyzenbeek)*

BS EN ISO 12947-2 / 180,000 Rubs (Martindale)*

*meets or exceeds

Hydrolysis:

16 Weeks

ASTM D3690 Sect. 6.11 (Hydrolytic Stability)

ISO 1419 Method C (Accelerated Ageing)

Colorfastness

Light:

AATCC 16.3, 200 Hours, Grade 4

ISO 105 B02, Grade 6

Crocking:

AATCC 8, Grade 4-5 Wet & Dry

Environmental

No intentionally added PFAS

SCS Indoor Advantage certified

REACH compliant

Does not contain any Red List chemicals



Scan QR code for a full list of specifications.

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.




ultrafabricsinc.com

Ultrafabrics® and logo are registered trademarks of Ultrafabrics Inc. Made in Japan.




Pumice — Ultrafabrics




497-0017 Whitewater



497-0047 White Shore




497-3260 Seahorse




497-6601 Coral Glow




497-4372 Dusk Green



497-6533 Hail



497-5969 Propeller




497-5203 Sunbeam



497-8279 Summer Melon




497-4373 Dusty Olive




497-2818 Blue Ice




497-5394 Pewter Cast




497-4018 Oar




497-8280 Aztec Clay




497-6534 Anchor Gray




497-2778 Hightide



Antimicrobial



Outdoor
Living



Recycled Bottles &
Renewable Fibers

Application

Interior Upholstery, Exterior Upholstery

Ideal for exterior marine seating and high exposure furniture applications

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface
65% Recycled Polyester, 35% FSC/PEFC
Certified Rayon Backing

Width:

54 Inches / 137 Centimetres

Repeat:

None

Performance

Abrasion:

ASTM D4157 / 400,000 Double Rubs (Wyzenbeek)*
BS EN ISO 12947-2 / 200,000 Rubs (Martindale)*

*meets or exceeds

Hydrolysis:

16 Weeks

ASTM D3690 Sect. 6.11 (Hydrolytic Stability)

ISO 1419 Method C (Accelerated Ageing)

Colorfastness

Light:

ASTM G154, 1000 Hours
SAE J2527 1500 kj, Grade 4
ISO 105 B02, Grade 8

Crocking:

AATCC 8, Grade 4-5 Wet & Dry

Chlorinated Water:

AATCC 162, Class 4-5

Perspiration:

AATCC 15, Class 5

Sea (Salt) Water:


AATCC 106, Class 4-5

Environmental

No intentionally added PFAS

SCS Indoor Advantage Gold certified

REACH compliant



Scan QR code for a full list of specifications.

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.



ultrafabricsinc.com


Ultrafabrics® and logo are registered trademarks of Ultrafabrics Inc. Made in Japan.




Summit — Ultrafabrics



421-3270 Barro



421-3357 Cream




421-3578 Stone



Antimicrobial



Outdoor
Living



Recycled Bottles &
Renewable Fibers

Application

Interior Upholstery, Exterior Upholstery

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface
65% Recycled Polyester, 35% FSC/PEFC
Certified Rayon Backing

Width:

54 Inches / 137 Centimetres

Repeat:

None

Performance

Abrasion:

ASTM D4157 / 400,000 Double Rubs (Wyzenbeek)*

BS EN ISO 12947-2 / 160,000 Rubs (Martindale)*

*meets or exceeds

Hydrolysis:

16 Weeks

ASTM D3690 Sect. 6.11 (Hydrolytic Stability)

ISO 1419 Method C (Accelerated Ageing)

Colorfastness

Light:

ASTM G154, 1000 Hours

SAE J2527 1500 kj, Grade 4

ISO 105 B02, Grade 8

Crocking:

AATCC 8, Grade 4-5 Wet & Dry

Chlorinated Water:

AATCC 162, Class 4-5

Perspiration:

AATCC 15, Class 5

Sea (Salt) Water:

AATCC 106, Class 4-5

Environmental

No intentionally added PFAS

SCS Indoor Advantage Gold certified

REACH compliant



Scan QR code for a full list of specifications.

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.



INDOOR ADVANTAGE GOLD
FURNITURE

ultrafabricsinc.com


Ultrafabrics® and logo are registered
trademarks of Ultrafabrics Inc. Made in Japan.




Tottori — Ultrafabrics



601-3885 Wild Truffle




601-3418 Origami White



601-3120 Udon



601-3885 Wild Truffle



601-3386 Desert Dune




601-3886 Natural Bark




601-3400 Soba



601-5037 Classic Grey



601-5020 Black Sesame



601-3297 Soy Sauce



601-3280 Tatami Mat



601-8282 Coral Reef




601-6026 Drizzle



601-5998 Rice Paper




601-8283 Burnt Ochre



601-1404 Rouge



601-6025 Hazy Sky



601-2622 Blue Mirage




601-3348 Ginseng



601-1459 Fig Jam



601-5033 Sand Castle




601-7249 Bali Bliss




601-8281 Amber Gold




601-9356 Faded Purple




601-2595 Hot Spring




601-4346 Dark Spruce




601-3300 Terrain



601-9362 Orchid



601-2515 Shibori Blue



601-4312 Lichen



Application

Interior Upholstery

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface
65% Recycled Polyester, 35% FSC/PEFC
Certified Rayon Backing

Width:

54 Inches / 137 Centimetres

Repeat:

None

Performance

Abrasion:

ASTM D4157 / 400,000 Double Rubs (Wyzenbeek)*

BS EN ISO 12947-2 / 200,000 Rubs (Martindale)*

*meets or exceeds

Hydrolysis:

16 Weeks

ASTM D3690 Sect. 6.11 (Hydrolytic Stability)

ISO 1419 Method C (Accelerated Ageing)

Colorfastness

Light:

AATCC 16.3, 200 Hours, Grade 4

ISO 105 B02, Grade 6

Crocking:

AATCC 8, Grade 4-5 Wet & Dry

Environmental

PFAS-free

SCS Indoor Advantage certified

REACH compliant

Does not contain any Red List chemicals



Scan QR code for a full list of specifications.

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.




ultrafabricsinc.com

Ultrafabrics® and logo are registered trademarks of Ultrafabrics Inc. Made in Japan.



Ultraleather — Ultrafabrics



291-2716 High Seas



291-0001 White



291-5714 Ice



291-5776 Classic Grey



291-5684 Arctic



291-5805 Ermine



291-5668 Silver Pearl



291-5666 Dove Grey



291-5676 Pelican



291-3286 Moth Wing



291-3601 Doe



291-5806 Schooner



291-5040 Elephant



291-5374 Flagstone



291-3602 Stone



291-1256 Papyrus



291-5607 Raven Wing



291-5708 Granite



291-5763 Charcoal



291-3287 Cocoa Nib



291-3666 Fudge



291-3700 Ivory



291-3599 Almond



291-3455 Milkweed



291-3851 Chamois




291-3612 Curry



291-3720 Light Oyster



291-3719 Champagne



291-3609 Buff




291-8272 Citronella



291-8271 Canyon Clay



291-3729 Tan



291-3850 Sand



291-3926 Cashmere



291-5250 Sassy



291-1412 Earthenware



291-3183 Pine Cone



291-3779 Taupe



291-3778 Pecan



291-8243 Apricot



291-1347 Poppy



291-3777 Walnut



291-3523 Cave



291-3610 Hide



291-8233 Autumn Leaf




291-1176 Red



291-7214 Boysenberry




291-2508 Rain Dance



291-2553 Cyan



291-4430 Eucalyptus




291-5200 Citrus



291-1311 Brick



291-2478 Diplomat Blue



291-2527 Lagoon



291-4314 Herbal Mist




291-4460 Parrot



291-1312 Chianti



291-2556 Admiral




291-2552 Riviera



291-2507 St. John




291-4366 Olive Leaf




291-3469 Garnet




291-2551 Baltic



291-2685 Bayou



291-7234 Emerald Isle




291-4454 Sonora




291-3205 Hot Chocolate



291-9385 Plum




291-2555 Nile



291-2509 Poseidon



291-4351 Shetland



Renewable
Fibers

Applications

Interior Upholstery

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface
100% FSC/PEFC Certified Rayon Backing

Width:

54 Inches / 137 Centimetres

Repeat:

None

Performance

Abrasion:

ASTM D4157 / 400,000 Double Rubs (Wyzenbeek)*
BS EN ISO 12947-2 / 180,000 Rubs (Martindale)*
*meets or exceeds

Hydrolysis:

16 Weeks
ASTM D3690 Sect. 6.11 (Hydrolytic Stability)
ISO 1419 Method C (Accelerated Ageing)

Colorfastness

Light:

AATCC 16.3, 200 Hours, Grade 4
ISO 105 B02, Grade 6

Crocking:

AATCC 8, Grade 4-5 Wet & Dry

Environmental

No intentionally added PFAS
SCS Indoor Advantage certified
REACH compliant
Does not contain any Red List chemicals



Scan QR code for a full list of specifications.

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.



ultrafabricsinc.com

Ultrafabrics® and logo, and Ultraleather® are registered trademarks of Ultrafabrics Inc. Made in Japan.




Ultraleather Anti-Static — Ultrafabrics



329-5810 Black



Anti-Static

Renewable
Fibers

Ultraleather Anti-Static

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface

100% FSC/PEFC Certified Rayon Backing

Weight:

Approx. 9.7 oz. Per Square Yard

Approx. 330 Grams Per Square Metre

Thickness:

Approx. 0.95 Millimetres

Width:

54 Inches / 137 Centimetres

Performance

Abrasion:

ASTM D4157 / 300,000 Double Rubs (Wyzenbeek)*

BS EN ISO 12947-2 / 180,000 Rubs (Martindale)*

*meets or exceeds

Hydrolysis:

16 Weeks

ASTM 3690 Sect. 6.11 (Hydrolytic Stability)

ISO 1419 Method C (Accelerated Ageing)

Adhesion of Coating: ASTM D751**Tear Strength:** ASTM D2261**Breaking Strength:** ASTM D751**Tensile Strength:** BS EN ISO 1421**Electrical Resistivity of Fabrics:** ASTM D257
 $\leq 10^7$ OHMS

Colorfastness

Light:

AATCC 16.3, 200 Hours, Grade 4

ISO 105 B02, Grade 6

Crocking:

AATCC 8, Grade 4.5 Wet & Dry

Flammability Requirements

- ASTM E84 (Adhered) - Class A
- CA TB 117-2013 - Pass
- FMVSS 302 - Pass
- NFPA 260 - Class 1
- UFAC - Class 1

These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under the fire test conditions of:

- ASTM E84 (Unadhered)
- BS 5852 Source 0, 1 & 5 (Cig, Match & Crib 5)
- IMO FTPC Part 8

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.

**ultrafabricsinc.com**

Ultrafabrics® and logo, and Ultraleather® are registered trademarks of Ultrafabrics Inc. Made in Japan.
12/24



Modern Textures



Statement Makers

For design-forward projects that demand something different. These future-focused textures have been crafted with the most advanced technology that delivers superior performance and a truly sensorial experience.

Eco Tech

Volar Bio

Wired



Eco Tech — Ultrafabrics



394-3801 Gypsum




394-6540 Whisper




394-3801 Gypsum





394-3622 Limestone



394-3709 Brownstone



394-4408 Komodo



Application

Interior Upholstery

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface

100% FSC/PEFC Certified Rayon Backing

Width:

54 Inches / 137 Centimetres

Repeat:

None

Performance

Abrasion:

ASTM D4157 / 150,000 Double Rubs (Wyzenbeek)*

BS EN ISO 12947-2 / 200,000 Rubs (Martindale)*

*meets or exceeds

Hydrolysis:

16 Weeks

ASTM D3690 Sect. 6.11 (Hydrolytic Stability)

ISO 1419 Method C (Accelerated Ageing)

Colorfastness

Light:

AATCC 16.3, 200 Hours, Grade 4

ISO 105 B02, Grade 6

Crocking:

AATCC 8, Grade 4-5 Wet & Dry

Environmental

No intentionally added PFAS

SCS Indoor Advantage certified

REACH compliant

Does not contain any Red List chemicals



Scan QR code for a full list of specifications.

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.



ultrafabricsinc.com

Ultrafabrics® and logo are registered trademarks of Ultrafabrics Inc. Made in Japan.



Volar Bio — Ultrafabrics



Proprietary Polycarbonate Biobased Blended Construction




630-8284 Onion Skin

Sustainability Without Sacrifice

Experience the future of sustainable design with Volar Bio, a breakthrough in high-tech performance fabrics. Containing 66% environmentally preferred materials, our multi-layer construction reduces dependence on finite resources while ensuring unmatched durability, easy maintenance, and a premium feel.

Volar Bio is not just another biobased fabric. This collection is built on a foundation of transparency and quality.

- 01 Repreve® Recycled Polyester:** Made from approximately 8 recycled plastic bottles per yard (9 recycled plastic bottles per linear meter), providing strength and resilience.
- 02 FSC/PEFC Certified ECOVERO™ Rayon:** Rapidly renewable rayon fibers that form a solid foundation.
- 03 Susterra® Propanediol Biobased Resin:** Sourced from U.S. dent corn, premium, certified resin reduces dependence on standard resources while maintaining uncompromising quality.
- 04 Indoor Advantage Gold Certified:** Ensuring clean indoor air quality.
- 05 29% USDA BioPreferred Program Certified:** A mark of verified biobased content.
- 06 REACH Compliant and Free of Red List chemicals:** Guaranteeing safety for human and environmental health.
- 07 Industry-leading performance:** 16-week hydrolysis resistance, 300,000 double rubs (Wyzenbeek), 200,000 rubs (Martindale).
- 08 Recognized excellence:** Interior Design Magazine HiP Award Winner - Environmental Impact, Hospitality Product, MetropolisLikes, and Interior Design Best of Year Environmental Impact Award.



630-6549 Silverstone




630-3592 Birch Bark




630-5877 Porcini




630-3842 Burlap



630-8252 Monarch



630-2837 Woad




630-7290 Mint




630-6018 Gravity




630-8284 Onion Skin



630-8287 Turmeric




630-2725 Macaw




630-4329 Matcha




630-5004 Fortress




630-3893 Bramble




630-1407 Scarlet



630-2749 Indigotin




630-4335 Spinach



630-6073 Pitch Black



630-8288 Walnut Shell




630-1472 Sumac




630-9446 Cabbage



630-8258 Café Noir



Bio-based
Ingredients



Recycled Bottles &
Renewable Fibers

Application

Interior Upholstery

General Specifications

Composition:

Proprietary Polycarbonate + Biobased Surface
65% Recycled Polyester, 35% FSC/PEFC
Certified Rayon Backing

Width:

54 Inches / 137 Centimetres

Repeat:

None

Performance

Abrasion:

ASTM D4157 / 300,000 Double Rubs (Wyzenbeek)*
BS EN ISO 12947-2 / 200,000 Rubs (Martindale)*
*meets or exceeds

Hydrolysis:

16 Weeks
ASTM D3690 Sect. 6.11 (Hydrolytic Stability)
ISO 1419 Method C (Accelerated Ageing)

Biobased Carbon Content:

29%
ASTM D6866-18 (Method B)
ISO 16620-2; 2015

Colorfastness

Light: AATCC 16.3, 200 Hours, Grade 4
ISO 105 B02, Grade 6
Crocking: AATCC 8, Grade 4-5 Wet & Dry

Environmental

PFAS-free
SCS Indoor Advantage certified
REACH compliant
Does not contain any Red List chemicals
Contains a 66% mix of environmentally preferred materials



Scan QR code for a full list of specifications.

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.




ultrafabricsinc.com

Ultrafabrics® and logo are registered trademarks of
Ultrafabrics Inc. Made in Japan.




Wired — Ultrafabrics



531-5309 Glisten Grey




531-3283 Butter Cookie



531-5266 Lemon Drop



531-2591 Baby Blue



531-6568 Faded Stone




531-3282 Milkshake




531-3284 Sugar Cone



531-8236 Marmalade



531-2592 Aquarius



531-6563 Dust




531-9421 Blackjack



531-3285 Kahlua




531-4306 Rio



531-2779 Hale Navy



531-9326 Acai



Applications

Interior Upholstery

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface
65% Recycled Polyester, 35% FSC/PEFC
Certified Rayon Backing

Width:

54 Inches / 137 Centimetres

Repeat:

27.55"V x 16.61"H / 700mm V x 422mm H

Performance

Abrasion:

ASTM D4157 / 400,000 Double Rubs (Wyzenbeek)*
BS EN ISO 12947-2 / 200,000 Rubs (Martindale)*
*meets or exceeds

Hydrolysis:

16 Weeks
ASTM D3690 Sect. 6.11 (Hydrolytic Stability)
ISO 1419 Method C (Accelerated Ageing)

Colorfastness

Light:

AATCC 16.3, 200 Hours, Grade 4
ISO 105 B02, Grade 6

Crocking:

AATCC 8, Grade 4-5 Wet & Dry

Environmental

No intentionally added PFAS
SCS Indoor Advantage Gold certified
REACH compliant
Does not contain Red List chemicals



Scan QR code for a full list of specifications.

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.



ultrafabricsinc.com

Ultrafabrics® and logo, are registered trademarks of
Ultrafabrics Inc. Made in Japan.



Uf Select



Swift & Stylish

Uf Select offers a fresh take on creativity and performance for today's competitive and time-sensitive projects. Featuring an inspiring array of textures and colors, this grouping is suitable for accessories, hospitality, residential, recreational vehicles, non-clinical healthcare, and workplace.

Impasto

Lino


Montage




Impasto — Uf Select®




733-00613 Ice Storm



733-60973 Almond Milk




733-60943 Arctic Fox



733-53513 Incense




733-35143 Snickerdoodle




733-58843 Thunder



733-73313 Golden Ochre



733-82683 Roasted Squash




733-27743 Bristle Blue



733-43553 Light Moss




733-34673 Tofu



733-33903 Amberglow




733-14263 Mahogany Red



733-27853 Deepwell




733-43393 Avocado



733-33853 Caribou



733-33343 Tiger Eye




733-14413 Firecracker




733-26053 Nocturne Blue




733-43563 Pine Needle




733-60983 Black Spinel




733-34863 Pumpernickel



733-93543 Kalamata



733-43403 Bay Leaf



733-72373 Genesis

Impasto — Uf Select®

Application

Interior Upholstery

General Specifications

Composition	Polycarbonate Blended Surface 65% Polyester, 35% Cotton Backing
Weight	Approx. 13.1 oz. Per Square Yard Approx. 445 Grams Per Square Metre
Thickness	Approx. 0.95 Millimetres
Width	54 Inches 137 Centimetres
Repeat	None

Performance

Abrasion	ASTM D4157 / 200,000 Double Rubs (Wyzenbeek)* BS EN ISO 12947-2 / 150,000 Rubs (Martindale)* *meets or exceeds
Hydrolysis	10 Weeks ASTM D3690 Sect. 6.11 (Hydrolytic Stability) ISO 1419 Method C (Accelerated Ageing)
Adhesion of Coating	ASTM D751
Tear Strength	ASTM D2261
Breaking Strength	ASTM D751
Seam Strength	ASTM D751 (Tack Tear)
Tensile Strength	BS EN ISO 1421

Colorfastness

Light	AATCC 16.3, 200 Hours, Grade 4 ISO 105 B02, Grade 6
Crocking	AATCC 8, Grade 4-5 Wet & Dry

Flammability Requirements

ASTM E84 (Adhered) - Class A | CA TB 117-2013 - Pass | FMVSS 302 - Pass | NFPA 260 - Class 1 | UFAC - Class 1 | AB 2998


For more information on our fabrics, cleaning and care instructions, please visit our website.

ultrafabricsinc.com

Ultrafabrics® and logo, and Uf Select® are registered trademarks of Ultrafabrics Inc. Made in Mexico.



Lino — Uf Select®



740-58733 Coin




740-34513 Haystack



740-34463 Cider



740-58733 Coin




740-82613 Yarrow




740-00503 White Marigold




740-65783 Wigwam




740-82593 Carrot



740-25143 Bosporous



740-43313 Granny Smith




740-50143 Ore




740-33793 Hearth



740-82603 Adobe Red



740-25123 Independence



740-43303 Verde



740-50193 Lead




740-34063 Trunk



740-13943 Plum Wine



740-43323 Jadite



740-43373 Pinenut

Lino — Uf Select®

Application

Interior Upholstery

General Specifications

Composition	Polycarbonate Blended Surface 65% Polyester, 35% Cotton Backing
Weight	Approx. 13.1 oz. Per Square Yard Approx. 445 Grams Per Square Metre
Thickness	Approx. 0.95 Millimetres
Width	54 Inches 137 Centimetres
Repeat	None

Performance

Abrasion	ASTM D4157 / 200,000 Double Rubs (Wyzenbeek)* BS EN ISO 12947-2 / 150,000 Rubs (Martindale)* *meets or exceeds
Hydrolysis	10 Weeks ASTM D3690 Sect. 6.11 (Hydrolytic Stability) ISO 1419 Method C (Accelerated Ageing)
Adhesion of Coating	ASTM D751
Tear Strength	ASTM D2261
Breaking Strength	ASTM D751
Seam Strength	ASTM D751 (Tack Tear)
Tensile Strength	BS EN ISO 1421

Colorfastness

Light	AATCC 16.3, 200 Hours, Grade 4 ISO 105 B02, Grade 6
Crocking	AATCC 8, Grade 4-5 Wet & Dry

Flammability Requirements

ASTM E84 (Adhered) - Class A | CA TB 117-2013 - Pass | FMVSS 302 - Pass | NFPA 260 - Class 1 | UFAC - Class 1 | AB 2998

These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under the fire test conditions of: BS 5852 Source 0, 1 & 5 (Cig, Match & Crib 5) | BS EN 1021 Part 1 & 2 (Cig & Match)

For more information on our fabrics, cleaning and care instructions, please visit our website.

Montage — Uf Select®



744-33373 Alpaca



744-00513 White Marble



744-35723 Jojoba



744-35733 Alfalfa



744-52783 Silver Birch



744-56303 Silver Ash



744-53503 Ganache



744-53493 Ghost




744-50393 Horseradish




744-35583 Oakmoss




744-60883 Cast Iron



744-60873 Gris



744-53473 Smoke Gray



744-35573 Acacia



744-53483 Beechnut



744-35593 String



744-73323 Chimera



744-14403 Mimosa



744-53453 Gull




744-43493 Grasshopper



744-35563 Cord



744-35553 Old Penny



744-93053 Passion Fruit



744-35033 Copen Blue



744-43503 Jalapeno



744-52173 Wax




744-82663 Chutney



744-93533 Mulled Wine



744-27873 Provence



744-43253 Sorrel




744-35673 Cinnamon Toast



744-14393 Tobacco Brown




744-14233 Red Rock



744-27863 Blue Graphite



744-43243 Balsam




744-36473 Cardamom




744-14223 Firebrick



744-14423 Poinsettia Red




744-26543 Bluestone



744-72353 Beryl




744-36513 Tarmac



744-82673 Orange Pepper



744-14453 Vivid Punch



744-25063 Indigo Batik



744-72313 Bluegrass

Montage — Uf Select®

Application

Interior Upholstery

General Specifications

Composition	Polycarbonate Blended Surface 65% Polyester, 35% Cotton Backing
Weight	Approx. 13.1 oz. Per Square Yard Approx. 445 Grams Per Square Metre
Thickness	Approx. 0.95 Millimetres
Width	54 Inches 137 Centimetres
Repeat	None

Performance

Abrasion	ASTM D4157 / 200,000 Double Rubs (Wyzenbeek)* BS EN ISO 12947-2 / 150,000 Rubs (Martindale)* *meets or exceeds
Hydrolysis	10 Weeks ASTM D3690 Sect. 6.11 (Hydrolytic Stability) ISO 1419 Method C (Accelerated Ageing)
Adhesion of Coating	ASTM D751
Tear Strength	ASTM D2261
Breaking Strength	ASTM D751
Seam Strength	ASTM D751 (Tack Tear)
Tensile Strength	BS EN ISO 1421

Colorfastness

Light	AATCC 16.3, 200 Hours, Grade 4 ISO 105 B02, Grade 6
Crocking	AATCC 8, Grade 4-5 Wet & Dry

Flammability Requirements

ASTM E84 (Adhered) - Class A | CA TB 117-2013 - Pass | FMVSS 302 - Pass | NFPA 260 - Class 1 | UFAC - Class 1 | AB 2998

These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under the fire test conditions of:
BS 5852 Source 0, 1 & 5 (Cig, Match & Crib 5) | BS EN 1021 Part 1 & 2 (Cig & Match)

For more information on our fabrics, cleaning and care instructions, please visit our website.