Reef Pro — **Ultrafabrics**



624-1413 Octopus



624-2632 Beluga





Reef Pro from Ultrafabrics

Application

Interior Upholstery

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface 65% Polyester, 35% Rayon Backing

Weight:

Approx. 12.1 oz. Per Square Yard Approx. 410 Grams Per Square Metre

Thickness:

Approx. 1.15 Millimetres

Width:

54 Inches / 137 Centimetres

Repeat:

None

Performance

Abrasion:

ASTM D4157 / 400,000 Double Rubs (Wyzenbeek)*
BS EN ISO 12947-2 / 200,000 Rubs (Martindale)*
*meets or exceeds

Hydrolysis:

16 Weeks

ASTM D3690 Sect. 6.11 (Hydrolytic Stability) ISO 1419 Method C (Accelerated Ageing)

Adhesion of Coating: ASTM D751

Tear Strength: ASTM D2261

Breaking Strength: ASTM D751

Tensile Strength: BS EN ISO 1421

Colorfastness

Light: AATCC 16.3, 200 Hours, Grade 4

ISO 105 B02, Grade 6

Crocking: AATCC 8, Grade 4-5 Wet & Dry

Flammability Requirements

· ASTM E84 (Adhered) - Class A

• CA TB 117-2013 - Pass

- FMVSS 302 Pass
- NFPA 260 Class 1
- UFAC Class 1

These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under the fire test conditions of:

• ASTM E84 (Unadhered)

• IMO FTPC Part 8

 BS 5852 Source 0, 1 & 5 (Cig, Match & Crib 5)

• BS EN 1021 Parts 1 & 2

Reef Pro Resists:

Ballpoint ink

Betadine

• Blood

Denim*

Mustard and Ketchup

Red Wine

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.





^{*} Removal of denim dye may vary depending on the period of time the stain sets in. While Pro offers excellent protection, full removal is not guaranteed.