Brisa Forecast — **Ultrafabrics**

Brisa Forecast combines beauty, comfort, and protection in one environment-flexible package. Climate control technology and breathability provide ultimate seating comfort and softness. Add in water repellency, solar endurance, and colorfastness, and Brisa Forecast becomes your go-to for outdoor residential applications.



- Superior durability industry-leading 16 weeks hydrolysis results
- In pursuit of our goal to include at least 50% renewable and/or recycled resources across all collections, the backcloth of Brisa Forecast will transition to include recycled polyester and responsibly sourced rayon.
 - 200,000 double rubs (Wyzenbeek), 140,000 rubs (Martindale)
 - Breathable technology promotes airflow for ultimate seating comfort
 - Bleach cleanable (1:5 bleach/water solution)

An intelligent solution – the Ultrafabrics family of performance fabrics highlights boundary-pushing innovation where looks, feel, and performance matter.

Recommended for residential outdoor applications only. Suitable for all indoor applications/markets.





Brisa Forecast from Ultrafabrics

Applications

Interior Upholstery, Exterior Upholstery

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface 65% Polyester, 35% Rayon Backing

Weight:

Approx. 11.5 oz. Per Square Yard Approx. 390 Grams Per Square Metre

Thickness:

Approx. 1.15 Millimetres

Width:

54 Inches / 137 Centimetres

Repeat: None

Performance

Abrasion:

ASTM D4157 / 200,000 Double Rubs (Wyzenbeek)* BS EN ISO 12947-2 / 140,000 Rubs (Martindale)* *meets or exceeds

Hydrolysis:

16 Weeks

ASTM D3690 Sect. 6.11 (Hydrolytic Stability) ISO 1419 Method C (Accelerated Ageing)

Adhesion of Coating: ASTM D751 Tear Strength: **ASTM D2261** Breaking Strength: ASTM D751 Tensile Strength: BS EN ISO 1421 Air Permeability: ASTM D737 Anti-mildew: ASTM G21

Sound Absorption: ASTM C423 FTM 5874 / CFFA 6a Cold Crack: Blocking: ASTM D751, 89-93

Colorfastness

Light: ASTM G154, 1000 Hours ISO 105 B02, Grade 8

Crocking: AATCC 8, Grade 4-5 Wet & Dry **Chlorinated Water:** AATCC 162, Class 4-5 Perspiration: AATCC 15, Class 5 Sea (Salt) Water: AATCC 106, Class 4-5

Flammability Requirements

- · ASTM E84 (Adhered) Class A
- · CA TB 117-2013 Pass
- FMVSS 302 Pass
- NFPA 260 Class 1
- UFAC Class 1

These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under the fire test conditions of:

• BS 5852 Source 0.1 & 5 ASTM E84 (Unadhered) • IMO FTPC Part 8 (Cig, Match & Crib 5)

• BS EN 1021 Parts 1 & 2

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.



