

# Brisa Frontier — Ultrafabrics


**Brisa Frontier**, a classic, relaxed grain colored with leather-inspired hues, is enhanced for use inside or out. Featuring our renowned breathable technology, this high-performing pioneer provides ultimate seating comfort and softness, while other enhancements include water repellency, EPA-registered mildew defense, solar endurance, and colorfastness. Brisa Frontier delivers ultimate flexibility and functionality.




- 
- Superior durability – industry-leading 14+ weeks hydrolysis results
  - Blended backcloth for expanded upholstery capabilities
  - 200,000 double rubs (Wyzenbeek), 100,000 rubs (Martindale)
  - Breathable technology promotes airflow for ultimate seating comfort
  - Bleach cleanable (1:5 bleach/water solution)

**An intelligent solution** – the Ultrafabrics family of performance fabrics highlights boundary-pushing innovation where looks, feel and performance matter.

Not for use in marine or contract exterior applications.



Outdoor Living



Breathable Comfort

# Brisa Frontier from Ultrafabrics

## Applications

Interior Upholstery, Exterior Upholstery

## General Specifications

### Composition:

100% Polycarbonate Polyurethane Surface  
65% Polyester, 35% Rayon Backing

### Weight:

Approx. 11.5 oz. Per Square Yard  
Approx. 390 Grams Per Square Metre

### Thickness:

Approx. 1.15 Millimetres

### Width:

54 Inches / 137 Centimetres

### Repeat:

8"V x 10.5"H / 203mm V x 267mm H

## Performance

### Abrasion:

ASTM D4157 / 200,000 Double Rubs (Wyzenbeek)\*  
BS EN ISO 12947-2 / 100,000 Rubs (Martindale)\*  
\*meets or exceeds

### Hydrolysis:

14+ Weeks  
ASTM D3690 Sect. 6.11 (Hydrolytic Stability)  
ISO 1419 Method C (Accelerated Ageing)

Adhesion of Coating: ASTM D751

Tear Strength: ASTM D2261

Breaking Strength: ASTM D5034

Tensile Strength: BS EN ISO 1421

Air Permeability: ASTM D737

Anti-mildew: ASTM G21

Sound Absorption: ASTM C423

Cold Crack: FTM 5874 / CFFA 6a

## Colorfastness

### UV:

ASTM G154, 1000 Hours

### Light:

AATCC 16.3, 200 Hours, Grade 4  
ISO 105 B02, Grade 6

### Crocking:

AATCC 8, Grade 4-5 Wet & Dry

### Chlorinated Water:

AATCC 162, Class 4-5

### Perspiration:

AATCC 15, Class 5

### Sea (Salt) Water:

AATCC 106, Class 4-5

## Flammability Requirements

- ASTM E84 (Adhered) - Class A
- CA TB 117 - Pass
- FMVSS 302 & 95/28 Annex IV - Pass
- NFPA 260 - Class 1
- UFAC - Class 1

These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under the fire test conditions of:

- ASTM E84 (Unadhered)
- BS 5852 Source 0, 1 & 5 (Cig, Match & Crib 5)
- IMO FTPC Part 8

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.



INDOOR ADVANTAGE GOLD FURNITURE

