



# Ultraleather® | Pro



**Ultraleather® | Pro** is crafted with passion and purpose. Imbued with optimal durability, protection and ease of care attributes, **Pro** maintains the **Ultraleather®** reputation as the softest polyurethane fabric in its class. Combined with a classic look highlighted by a well-balanced mix of color options, this collection's enduring construction is the preferred high-performance choice for the most active settings.

The reasons as to why **Pro** sits at the top of so many project lists include:

- Enduring performance (14+ weeks hydrolysis results)
- Mishaps happen - in the form of ballpoint pens, red wine, mustard, denim dyes, and iodine-based stains often encountered in the healthcare sector. Stains are a thing of the past thanks to this innovative repellency
- Inherent EPA-registered antimicrobial protection for added defense
- Engineered to out-perform the highest levels of abrasion resistance
- Ease of care

**Pro** is infused with power and comfort combined, taking durability and luxury to the next level.



Ink & Stain Resist



Antimicrobial Resist

# Ultraleather® | Pro

## General Specifications

### Composition:

100% Polycarbonate Polyurethane Surface  
100% Reinforced Rayon Backing

### Weight:

Approx. 9.7 oz. Per Square Yard  
Approx. 330 Grams Per Square Metre

### Thickness:

Approx. 0.95 Millimetres

### Width:

54 Inches / 137 Centimetres

## Performance

### Abrasion:

ASTM D4157 / 500,000 Double Rubs (Wyzenbeek)\*  
BS 2543 / 200,000 Rubs (Martindale)\*

\*meets or exceeds

### Hydrolysis:

14+ Weeks  
ASTM D3690-02 Sect. 6.11 (Hydrolytic Stability)  
ISO 1419 Method C (Accelerated Ageing)

### Adhesion of Coating:

ASTM D751

### Tear Strength:

ASTM D2261

### Breaking Strength:

ASTM D5034

### Antimicrobial:

ASTM E2180

## Colorfastness

### Light Fastness:

AATCC 16.3, 200 Hours, Grade 4-5

### Crocking:

AATCC 8, Class 5 Wet & Dry

## Flammability

### F/R Rating:

- ASTM E84 (Adhered) - Class A
- CA TB 117-2013 - Pass
- FMVSS 302 & 95/28 Annex IV - Pass
- NFPA 260 - Class 1
- UFAC - Class 1

### Other Tests\*:

- ASTM E84 (Unadhered)
- BS 5852 PT 0, 1 & 5 (Crib 5)
- BS 5867 Part 2 Type B
- BS 7175
- California Technical Bulletin 133
- FAR Specifications
- IMO A.652 (16)
- NFPA 701

\*These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under these fire test conditions.

## Earth Friendly

### • GREENGUARD Certified

- Meets stringent chemical emission limits for various VOCs (ex. Formaldehyde)
- Promotes healthier indoor air quality
- Contributes towards satisfying credits under LEED® and BIFMA

- Compliant with Prop 65
- Less than 100 ppm of EPA-registered antimicrobial treatment
  - No Triclocarban or Triclosan
- No Bisphenol A (BPA)
- No Conflict Minerals
- No Flame Retardants (Halogenated, Brominated: ex. PBDEs)
- No Heavy Metal Stabilizers
- No Plasticizer Phthalates
- No POPs (Persistent Organic Pollutants)
- No PVC (Polyvinyl Chloride)
- No toxic by-products
- Over 99% of solvents recaptured and recycled

## Ultraleather® | Pro resists:



Ballpoint ink



Betadine



Blood



Denim\*



Mustard/ketchup



Red Wine

\*Removal of denim dye may vary depending on the period of time the stain sets in. While Pro offers excellent protection, full removal is not guaranteed.

For more information on our fabrics, cleaning and care instructions, please visit our website.



PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS: UL.COM/GG UL 2818

Ultrafabrics® and logo, and Ultraleather® are trademarks of Ultrafabrics Inc. Made in Japan.

ultrafabricsinc.com



7/18